

# RCI Plus 2 GEN2 1.050 for Benelli Monotube [www.ROTHPerformance.com](http://www.ROTHPerformance.com)

## Installation Instructions

**WARNING: For all models available, first and foremost, make sure your gun is clear of all ammunition and in a safe condition.**

Please read ALL instructions before beginning. Always wear safety glasses when working on your gun.

1. Remove your existing RCI Monotube cap, spring, and follower.
2. Add Vibra Tight VC-3 or similar to threads on the monotube to prevent Plus 2 from loosening during Shooting.
3. Replace follower and spring. Thread Plus two onto monotube.
4. Tighten to a dead stop
5. Installation is complete.

All Roth Concept Innovations ("RCI") products have a 1 year limited warranty. The warranty applies towards defects in materials or workmanship. Any repairs or modifications not done by RCI voids any warranty.

Disclaimer - ALWAYS PRACTICE SAFE FIREARM HANDLING!!! DO NOT POINT GUN AT YOURSELF OR ANYONE ELSE, EVEN WHEN LOADING! KEEP HANDS CLEAR OF BARREL! Roth Concept Innovations LLC is not responsible for any accidents/injuries that could occur while mishandling/misusing any of our products, or any other unsafe actions performed by user, including but not limited to: unsafe firearm handling. WHEN LOADING GUN, HAVE SAFETY ON! DO NOT LOAD AMMUNITION IN CHAMBER UNTIL YOU ARE READY TO FIRE. IN CASE OF MECHANICAL ISSUES WITH YOUR GUN or any RCI Products, REMEMBER TO ALWAYS MAKE SURE YOUR GUN IS SAFE BEFORE ADDRESSING ANY ISSUES (i.e. EMPTY CHAMBER)!

Disclaimer - U.S. Regulations: It is your responsibility to know and follow All, Federal, State and local gun laws regarding owning, possessing, using, buying, selling, distributing, or any other aspect in respects of Roth Concept Innovation's products.

Disclaimer - RCI is in NO way responsible for damage to your gun.

# RCI Plus 2 GEN2 1.050 for Benelli Monotube [www.ROTHPerformance.com](http://www.ROTHPerformance.com)

## Installation Instructions

**WARNING: For all models available, first and foremost, make sure your gun is clear of all ammunition and in a safe condition.**

Please read ALL instructions before beginning. Always wear safety glasses when working on your gun.

1. Remove your existing RCI Monotube cap, spring, and follower.
2. Add Vibra Tight VC3 or similar to threads on the monotube to prevent Plus 2 from loosening during Shooting.
3. Replace follower and spring. Thread Plus two onto monotube.
4. Tighten to a dead stop
5. Installation is complete.

All Roth Concept Innovations ("RCI") products have a 1 year limited warranty. The warranty applies towards defects in materials or workmanship. Any repairs or modifications not done by RCI voids any warranty.

Disclaimer - ALWAYS PRACTICE SAFE FIREARM HANDLING!!! DO NOT POINT GUN AT YOURSELF OR ANYONE ELSE, EVEN WHEN LOADING! KEEP HANDS CLEAR OF BARREL! Roth Concept Innovations LLC is not responsible for any accidents/injuries that could occur while mishandling/misusing any of our products, or any other unsafe actions performed by user, including but not limited to: unsafe firearm handling. WHEN LOADING GUN, HAVE SAFETY ON! DO NOT LOAD AMMUNITION IN CHAMBER UNTIL YOU ARE READY TO FIRE. IN CASE OF MECHANICAL ISSUES WITH YOUR GUN or any RCI Products, REMEMBER TO ALWAYS MAKE SURE YOUR GUN IS SAFE BEFORE ADDRESSING ANY ISSUES (i.e. EMPTY CHAMBER)!

Disclaimer - U.S. Regulations: It is your responsibility to know and follow All, Federal, State and local gun laws regarding owning, possessing, using, buying, selling, distributing, or any other aspect in respects of Roth Concept Innovation's products.

Disclaimer - RCI is in NO way responsible for damage to your gun.